

FUNCTIONAL PD-602

COLD-FLOW IMPROVER for GROUP I MINERAL OIL-BASED LUBRICANTS

APPLICATION:

FUNCTIONAL PD-602 is a wax-crystal modifier. Its primary use is in improving the cold flow properties of mineral oil-based lubricants at temperatures below their cloud points. It is effective under both rapid-cooling conditions and extended cold storage conditions. **FUNCTIONAL PD-602** is effective in hydraulic fluids, chain saw oils, pneumatic-tool lubricants and other lubricants made from solvent extracted neutral base stocks as well as hydro-cracked base stocks

COMPOSITION:

The active additive in **FUNCTIONAL PD-602** is a proprietary polymer. The diluent oil in **FUNCTIONAL PD-602** is light paraffinic oil.

Typical properties	
Appearance	light-colored liquid
Odor	mild fatty
Specific Gravity	0.91
Lbs per Gallon	7.33
Flash Point	150°C min.
Kinematic Viscosity	<800 cSt at 100°C

TREATMENT LEVEL:

To reduce the pour point of a Group I mineral oil to below -36°C, a treatment of 0.125% is usually sufficient.. Since the responsiveness of oil to wax-crystal modifiers is extremely variable and may be dependent on the cooling history, the user best determines the best treatment level.

HANDLING:

Any convenient technique may be used for blending. Safe handling precautions are the same as those to be taken with vegetable oils; see the current Material Safety Data Sheet.

This Technical Data Sheet and the Material Safety Data Sheet contain information believed to be accurate and reliable. No warranty is made, however, to information beyond the control of FUNCTIONAL PRODUCTS INC. The engineering and management personnel of the user are responsible for determining the suitability of this or any product for any specific application, and this information is offered to them for that purpose.

5/26/2009