

FUNCTIONAL V-198A TACKIFIER

APPLICATION:

FUNCTIONAL V-198A is an additive that confers a tack or stringiness to a lubricant. It may be used to provide adherence in way oils and chain lubricants, stringiness in greases, and aerosol resistance in mist and pneumatic-system lubricants. Diluted versions of **FUNCTIONAL V-198A** are available for lower viscosity and easier handling.

COMPOSITION:

The active polymeric ingredient in **FUNCTIONAL V-198A** is a polyisobutylene long-used in tackifiers. The diluent oil in **FUNCTIONAL V-198A** is light colored paraffinic oil that does not require hazard labeling.

Typical Properties	
Specific Gravity	0.86
Lbs per Gallon	7.20
Flash Point	149 °C (300 °F)
Kinematic Viscosity	4,600 – 5,500 cSt at 100 °C
Color	yellow-orange (<3 ASTM)

TREATMENT LEVEL:

A starting treatment level for a way lube is 0.25%. For chain lubes the treatment range is 0.25% to 1.0%. Minimization of hydrocarbon aerosol escape from mist-lubricated and pneumatic equipment requires about 0.5% in the mist oil. The best treatment level for greases is left to the formulator. Since there are no standardized test methods for these properties, the required treatment level is best determined by experimentation by the user.

HANDLING:

Due to the viscosity of **FUNCTIONAL V-198A**, elevated temperature (about 150°F (65°C)) can facilitate handling, but temperatures over 200°F (95°C) should be avoided. Where higher temperatures or high shear are encountered, **FUNCTIONAL V-188** is recommended instead. Safe handling precautions are the same as those to be taken with the base oil; see the current MSDS. The tackiness of the resulting lubricant can be lessened by shearing, so mechanical shearing during blending and handling should be minimized.

This Technical Data Sheet and the Material Safety Data Sheet contain information believed to be accurate and reliable. No warranty is made, however, to information beyond the control of FUNCTIONAL PRODUCTS INC. The engineering and management personnel of the user are responsible for determining the suitability of this or any product for any specific application, and this information is offered to them for that purpose.

1/4/2011

Functional Products, Inc. 8282 Bavaria Rd. Macedonia, OH 44056

Ph: 330-963-3060 Fax: 330-963-3322

QMS certified to ISO 9001:2008